

Фотометры/колориметры ProMetric Y

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

ProMetric® Y

Imaging Photometer



Purpose-built for manufacturing test of displays, illuminated keyboards, and surfaces.

ProMetric Y Highlights

- **Display Test:**
Inspect for particle and line defects, uniformity, light leakage, mura, demura (pixel correction), luminance, surface defects (bubbles, scratches, debris).
- **Cosmetic Defects:**
Detect scratches, dings, dents, missing / disoriented elements, confirm text, evaluate overall surface uniformity.
- **Keypad Inspection:**
Evaluate brightness, inter- and intra-character uniformity, light leakage, missing character, wrong character.

Key Features

- Optimized for speed, resolution, and measurement accuracy
- Available in photometric and radiometric models
- Multiple lens choices for a wide range of focus and aperture settings
- Seamless integration with TrueTest™ and other specialized software



Fast, small-format imaging photometer optimized for display and cosmetic inspection in production

The ProMetric® Y family of rugged, small-form-factor imaging photometers is optimized to test displays, keyboards, assemblies, and cosmetic surfaces in high-volume production settings. The sophisticated measurement performance of this photometer combined with configurable analysis software and local engineering expertise delivers a complete production test solution. Faster measurements enable shorter cycle times. Objective quantification replaces subjective human inspection to reduce operating costs. Reliable test analyses improve yield. Deploying a ProMetric Y system increases output, improves quality, and controls cost to deliver a quick return on your production test investment.

Each ProMetric Y Imaging Photometer employs a scientific-grade image sensor that provides accurate, repeatable measurements. ProMetric cameras optimize resolution and dynamic range to ensure imaging performance. ProMetric Y supports high-speed USB and/or Ethernet communications.

ProMetric Y incorporates industry-first **Smart Technology™** innovations, which simplify setup and ensure accurate measurement results.

- **Smart Control™** for fast, precise setup: Smart Control allows users to electronically adjust both focus and aperture settings of the lens.
- **Smart Calibration™** for automatic high-accuracy results: ProMetric Y offers a variety of electronically controlled lenses, each calibrated over a wide range of working distances and aperture settings. ProMetric Y monitors focal distance and aperture settings and automatically applies the correct flat-field calibration.

ProMetric Y comes standard with ProMetric Software to operate the photometer in a manual mode or to support programming via an API. ProMetric Y is optimized for automation via optional TrueTest™ Automated Visual Inspection Software and a range of application-specific software modules. TrueTest Software provides a complete, turnkey solution for high-volume manufacturing of display devices (televisions, phones, tablets, notebooks), backlit symbols (keyboards, instrument panels), virtual projections (augmented reality and head-up displays), and lighting products.

Specifications

Parameter	ProMetric Y2	ProMetric Y29	ProMetric Y43	ProMetric Y45	ProMetric Y61
Primary Application	Production, Lighting	Production, Display Testing, Pixel-level Measurement, Advanced Vision			
Sensor Pixel Resolution	1600 x 1200	6576 x 4384	8040 x 5360	8192 x 5460	9568 x 6380
Sensor Megapixels	1.9	28.8	43.1	44.7	61.0
Sensor Type	CCD			CMOS	
System Dynamic Range (single exposure, per pixel)	59 dB (1 x 1 binning)			66 dB (1 x 1 binning)	76 dB (1 x 1 binning)
Luminance (Minimum)*	0.00001 cd/m² Limit of Detection 0.0001 cd/m² @ SNR = 60 0.0005 cd/m² @ SNR = 100			0.0001 cd/m² Limit of Detection 0.0002 cd/m² @ SNR = 60 0.0005 cd/m² @ SNR = 100	0.0005 cd/m² Limit of Detection 0.0010 cd/m² @ SNR = 60 0.0015 cd/m² @ SNR = 100
Luminance (Maximum)	10 ¹⁰ cd/m² with optional ND filters				
System Accuracy**	Illuminance ± 3%; Luminance (Y) ± 3%				
Short-term Repeatability*	Illuminance ± 0.02%; Luminance (Y) ± 0.02%			Illuminance ± 0.04%; Luminance (Y) ± 0.04%	Illuminance ± 0.02%; Luminance (Y) ± 0.02%
Lens Type	Electronically controlled focus and aperture				
Focal Distances Available	24, 35, 50, 100, 200 mm	35, 50, 100, 200 mm			
Field of View (Full Angle, H x V degrees)	24 mm 20° x 15° 35 mm 14° x 10° 50 mm 10° x 8° 100 mm macro 5° x 4° 200 mm 3° x 2°	35 mm 55° x 37° 50 mm 40° x 28° 100 mm macro 20° x 14° 200 mm 11° x 7°		35 mm 40° x 27° 50 mm 29° x 19° 100 mm macro 15° x 10° 200 mm 8° x 5°	35 mm 55° x 37° 50 mm 40° x 28° 100 mm macro 20° x 14° 200 mm 11° x 7°
Minimum Measurement Time***	0.2 sec	1.0 sec	1.4 sec	0.5 sec	0.6 sec
Spatial Measurement Capabilities	Luminance, Radiance, Illuminance, Irradiance, Luminous Intensity, Radiant Intensity				
Units	foot-lambert, cd/m², nit, W/sr/m², foot-candles, lux, lux-s, W/m², W-s/m², candela, W/sr				
Communication Interface	Ethernet 100/1000, USB 2.0			10 Gigabit Ethernet (10 GigE)	
Power	External AC / DC adapter, 100-240 V, 50-60 Hz, 60 Watts				
Dimensions (H x W x D)	86 mm x 86 mm x 154 mm				86 mm x 86 mm x 170 mm
Weight	1.4 kg				1.2 kg
Operating Temperature	0 - 30° C			15 - 35° C	5 - 35° C
Operating Humidity	20 - 70% non-condensing				

Specifications subject to change without notice.

- * Based on a virtual detector size of 100 x 100 pixels.
- ** Based on illuminant A or user calibration for specific spectra. Based on a virtual detector size of 100 x 100 pixels and a minimum exposure time of 10ms.
- *** For 100 cd/m², using Ethernet.

ProMetric Y-series imaging photometers, and the electronically controlled lenses supplied with them, are factory-calibrated over all possible distances and two specific aperture settings. Because the lenses are electronically controllable for focus (working distance) and aperture, the photometer will automatically apply the appropriate flat-field correction.

Lens	Calibrated Apertures
Canon EF 24 mm f/2.8 USM	f/4.7 f/8
Canon EF 35 mm f/2.0 USM	f/2.3 or f/4.0† f/8
Canon EF 50 mm R f/2.0 USM	f/2.8 f/8
Canon EF 100 mm f/2.8L Macro IS USM	f/3.3 f/8
Canon EF 200 mm f/2.8 USM	f/3.3 f/8

† f/4.0 for 29MP, 43MP, and 61MP systems



System Specifications

- Intel® Core™ i7-8086 CPU @ 4.00 GHz
- 32 GB installed RAM

System Requirements

- Windows® 10, 64 bit
- Ethernet 100/1000 or USB 2.0 port (Y2, Y29, and Y43)
- Desktop: PCI-E x8 lane slot (Y45, Y61)
- Laptop: Thunderbolt 3 Port (Y45, Y61)

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93